



REVISION DATA		
REV	DESCRIPTION	DATE
A0	NEW DRAWING	2014-03-14

Technical Data

Material:
 Contact Material: Brass
 Contact plating: See the part NO.
 Insulator Material: Black Polyester UL94V-0
 Standard: See the part NO.

Electrical:
 Current rating: 3.0Amps/contact max.
 Contact resistance: ≤20mΩ/contact
 Insulation resistance: ≥1000MΩ at V=100V
 Withstanding Voltage: 1000V AC/minute

Mechanical:
 Mechanical life cycle: min.200
 Operating temperatures: Gold Plated: -55°C to +105°C
 Tin plated: -40°C to +105°C
 Soldering temperature: +260°C, 10s max. (PA6T)

P.C.B LAYOUT

P120	22	XXX	XX	R	X	X	N	R015
Product Descriptions P120	Product Type 22 Dual Row Dual Base	No. of Positions XXX Poles	Pin Plating G0 Gold Flash SN Tin Plated	Angle options R Ringht Angle	Insulator Material A PBT+G/F30% B PA66+G/F30% C PA6T+G/F30% D LCP+G/F30%	Color B Black W White L Blue G Green Y Yellow R Red N Natural		Pin length(mm) L=19.3/ 24.35mm

ANYCONN® 东莞市恩康电子有限公司
 www.enkcom.com **DONGGUAN ANYCONN ELECTRONICS CO.,LTD**

TOLERANCE	PROJECTON		TITLE: 2.54mm Pin Header Double Row Right Angle Pin Length 19.3/ 24.35mm
ANGLE ±5°	DATE :	2014-03-14	PART NO: P12022XXXXRXXR015
X.XXX ±0.05	DRAWN :	LSJ	
X.XX ±0.10	CHECKED :		DRAWING NO: EP-P12022-011
X.X ±0.15	APPROVED :		REV: A0 UNIT: mm SCALE: 1:1 SIZE: A4
X. ±0.20			