



PCB LAYOUT

REVISION DATA		
REV	DESCRIPTION	DATE
A0	NEW DRAWING	2012-10-26

Technical Data

Material:
 Contact Material: Brass
 Insulator Material: Black Polyester UL94V-0
 Standard: See the part NO.

Electrical:
 Current rating: 1.0Amps/contact max.
 Contact resistance: ≤20mΩ/contact
 Insulation resistance: ≥1000MΩ at V=100V
 Withstanding Voltage: 300V AC/minute

Mechanical:
 Operating temperatures: Gold Plated: -55°C to +105°C
 Tin plated: -40°C to +105°C
 Soldering temperature: +260°C, 10s max.

P115	11	XXX	XX	D	X	X	N	DXXX
Product Descriptions P115 H=2.5	Product Type 11 Single row	No. of Positions XX Poles	Pin Plating G0 Gold Flash SN Tin Plating G2 Gold2u" G3 Gold5u" G4 Gold10u" G5 Gold15u" G6 Gold30u"	Angle options D Straight	Insulator Material A PBT B Nylon-66 C Nylon-6T D LCP E Nylon-46	Color B 黑色 W 白色 L 蓝色 G 绿色 Y 黄色 R 红色 N 本色	Insulator Options N 无柱 O 外柱 W 内柱 F 带防呆点 C 侧柱	Pin length(mm) L=9.04mm

ANYCONN® 东莞市恩康电子有限公司
 www.enkcom.com **DONGGUAN ANYCONN ELECTRONICS CO.,LTD**

TOLERANCE	PROJECTON		TITLE: PH1.27 H2.50mm Single Row Straight L9.04mm Pin Header
ANGLE ±5°	DATE :	2012-10-26	PART NO: P11511XXXXDXXNDXXX
X.XXX ±0.10	DRAWN :	kanggc	DRAWING NO: EP-P11511-011
X.XX ±0.20	CHECKED :		REV: A0 UNIT: mm SCALE: 3:1 SIZE: A4
X.X ±0.30	APPROVED :		
X. ±0.50			